GM-M03, L1/L5 Dual-band, Multi-satellite Systems, GNSS Module to support NavIC

RoHS Compliant



Overview

Based on the AG3335 chip by 12nm technology, GM-M03 is able to concurrently track L1 band signals from all civil navigation systems, i.e. GPS, GLONASS, GALIELO, BEIDOU, QZSS. In addition, L5 band NavIC signal is also concurrently tracked. Thanks to this capability, positioning becomes easy even in the typical GPS difficult environments.

GM-M03 is an all-in-one GNSS smart antenna module that includes antenna, LED, connector, and all circuits necessary for sub-meter positioning.

Applications

- Navigation (autos, trains, boats, pedestrians etc.)
- ELD (Electronic Logging Device)
- Timing (precise clock, FEMTO cell, traffic lights etc.)

Features

- Based on the 12nm technology AG3335 chip
- 135 channels, tracks all civil navigation systems
- Concurrent tracking of positioning satellites
  - L1: GPS, GLONASS, GALILEO, BEIDOU, QZSS, SBAS
  - SBAS ranging (WAAS, EGNOS, MSAS, GAGAN)
  - L5: NAVIC
- High performance: -165dBm tracking sensitivity
- Support of smart jammer detection on GPS, GLONASS, Galileo, BEIDOU bands.
- 12 multi-tone AIC (active interference canceller) in both L1/L5 bands for removing unwanted signals.
- Indoor and outdoor multi-path detection and compensation
- PPS of ±10ns accuracy with adjustable duty cycle
- Up to 10Hz update rate
- RTCM ready (v2.3 and v3.3)
- AGPS/AGNSS
  - EPO™ (Extended Prediction Orbit) orbit prediction
  - EASY™ (Embedded Assist System) self-generated orbit prediction
- LOCUS™ logger function
- All-in-one, plug-n-play smart antenna module
  - Built-in L1/L5 dual-band G3B= GNSS antenna
  - Built-in wire-to-board digital connector
  - Built-in LED for position fix indication
  - Built-in UART/RS232 option
- External backup power option via I/O pin is available for special application of high working temperature.
- Fully EMI shielded
- Industrial operating temperature range: -40 ~ 85℃

Note: ™ Airoha trade mark

=G3B: GPS/GLONASS/GALILEO/BEIDOU

Technical Specifications

Receiver Performance Data+

Receiver Type	135 channels,

Navisys Technology Corp.
Tel : +886-3-5632598
Sales contact: sales@navisys.com.tw
Address:2F, No.56, Park Ave. II, Hsinchu Science Park, 30844, Taiwan (R.O.C.)
https://www.navisys.com.tw/
Fax: +886-3-5632597
Technical support: service@navisys.com.tw

	L1: 1602 MHz: GLONASS:L1OF 1575.42 MHz GPS & QZSS: L1 C/A SBAS: L1 QZSS L1 SAIF Galileo: E1 (E1B+E1C) 1561.098 MHz BEIDOU B1I L5: 1176.45 MHz NAVIC SPS
Horizontal Position Accuracy	2.5m (50% 24hr static, -130dBm)
Vertical Position Accuracy	3.75m (50% 24hr static, -130dBm)
Velocity Accuracy	<0. 05 m/s (speed, autonomous) (50%@30m/s)
Time To First Fix Cold start	Autonomous (50% -130dBm) 24sec
Sensitivity (Autonomous)	Acquisition: -148dBm Tracking: -165dBm
Max. Update Rate	10Hz (default 1Hz)
Max. Altitude	<18,000 m
Max. Velocity	<1,852 km/hr
Protocol Support	NMEA V3.01 & V4.10 GGA, GSA, GSV, RMC, VTG UART: N-8-1 38400/115200(default)/921600bps Proprietary PAIR command Proprietary Binary sentence
SBAS Support	WAAS, EGNOS, MSAS,GAGAN
AGPS/AGNSS	● EPO data: GPS, GLONASS ● QEPO data: GPS, GLONASS, GALILEO, BEIDOU ● EASY: GPS
Dynamics	<4g

+ Note. According to IC Spec

Electrical Data

Power Supply (VCC)	3 ~ 5 V
Power Consumption	75±5mA/USB, 50 SVs used in fix
Backup Power (V_BAT)	2~5 V
TTL I/O	V_{IH}: 2~3.15V, V_{IL}: 0~0.8V V_{OH}: >2.1V, V_{OL}< 0.72V


Environmental Data

Operating temperature	-40 ~ 85℃ except
Storage temperature	-40 ~ 85℃ except
Vibration	5Hz to 500Hz, 5g
Shock	Half sine 30g/11ms

Mechanical Data (mm)

30 x 30 x 11.8

6-pin Interface, pitch 1.0mm



Ordering Information

GM-M03R

Pin	Name	Function	I/O
1	GND	Ground	Input
2	VCC	Power supply	Input
3	TXD-TTL	TTL level serial data output	Output
4	RX-RS232	RS232 level serial data input	Input
5	TX-RS232	RS232 level serial data output	Output
6	RXD-TTL	TTL level serial data input	Input

GM-M03T

Pin	Name	Function	I/O
1	GND	Ground	Input
2	VCC	Power supply	Input
3	TXD-TTL	TTL level serial data output	Output
4	PWR_CTRL	Power control, high/floating: ON, low: OFF	Input
5	1PPS-TTL	Pulse Per Second signal	Output
6	RXD-TTL	TTL level serial data input	Input

Navisys Technology Corp. https://www.navisys.com.tw/
Tel : +886-3-5632598 Fax: +886-3-5632597
Sales contact: sales@navisys.com.tw Technical support: service@navisys.com.tw
Address:2F, No.56, Park Ave. II, Hsinchu Science Park, 30844, Taiwan (R.O.C.)

GM-M03U/W

Pin	Name	Function	I/O
1	GND	Ground	Input
2	VCC	Power supply	Input
3	D+	USB D+	I/O
4	D-	USB D-	I/O
5	1PPS-TTL	Pulse Per Second signal	Output
6	PWR_CTRL	Power control, high/floating: ON, low: OFF	Input

Note. W connects DCD to 1PPS while U doesn't.

GM-M03Q

Pin	Name	Function	I/O
1	GND	Ground	Input
2	VCC	Power supply	Input
3	TX-RS232	Serial data output	Output
4	RX-RS232	Serial data input	Input
5	1PPS-RS232 [$&]	Pulse Per Second signal/ or	Output
6	NC	No connection	-

[$] TTL level could be customized

[&] Please be noted that the RS232 line transceiver would introduce 0.3 us pulse skew to the 1PPS signal of RS232 model.

* This document is subject to change without notice.

Navisys Technology Corp. https://www.navisys.com.tw/
Tel : +886-3-5632598 Fax: +886-3-5632597
Sales contact: sales@navisys.com.tw Technical support: service@navisys.com.tw
Address:2F, No.56, Park Ave. II, Hsinchu Science Park, 30844, Taiwan (R.O.C.)